

No	1	2	3	4	5
Motherboard	ASUS P4B533-VT	ASUS P4C800	MSI 875P Neo LSR (MS6758)	Gigabyte GA-8KNXP	Gigabyte GA-8PE800Ultra
Chipset	845G (North Bridge) ICH4 (South Bridge)	875P (North Bridge) ICH5 (South Bridge)	875P (North Bridge) ICH5 (South Bridge)	875P (North Bridge) ICH5R (South Bridge)	845PE (North Bridge) ICH4 (South Bridge)
CPU	Intel 2.4GHz (FSB 533)	Intel 2.8CGHz (FSB 800)	Intel 2.4CGHz (FSB 800)	Intel 2.6CGHz (FSB 800)	Intel 3.06GHz (FSB 533)
VGA	Gigabyte GV-AV64S-T (ATi RADEON 7000)	ASUS (V9520) (128M) FX5200	MSI (MS8907) (128M) FX5200 TDR128	PowerColor R95V-C3L (ATi RADEON R9500)	Gainward GeForce4 MX440
RAM	Kingston 256MB DDR266	Transcend 256MB DDR400 x 2	Transcend 256MB DDR400 x 2	Kingston 256MB DDR400 x 2	Kingmax 512MB DDR333
HDD	Maxtor 40GB	Seagate 80G	Maxtor 80 GB (8M cache)	Seagate 80 GB	Maxtor 80 GB
H/W	GV800 V1.07 card	GV600 V2.08A card GV900 V1.11 card GV1000 V1.11 card	GV600 V2.08 card	1.GV600 V2.11 card 2.GV900 V1.11 card 2.GV900-8V1.11 card 4. GV1000 V1.11+ DSP G1+GVA16	GV750 V1.07 card
S/W	V5300 V5401	V5300 V5400	V5300	V5300 V5400 V6000	V5300
O/S	English Windows 2000 Windows XP	English Windows XP	English Windows XP	English Windows XP	English Windows 2000
Test Period	7 days (05/19~05/26) 18 days (1/15~2/2)	12 days (05/27~06/08) 7 days (8/29~9/5)	8 days (05/27~06/04)	7 day(05/23~05/30) 9 days (8/29~9/7) 22 days (1/16~2/7)	12 days (05/27~06/08)
Recording Mode	Round-The-Clock	Round-The-Clock	Round-The-Clock	Round-The-Clock	Round-The-Clock
CODEC	Wavelet Mpeg4	Wavelet M-Jpeg	Wavelet	Wavelet GeoMpeg4	Wavelet
Frames / Sec	Smart Record Technology	Smart Record Technology 230~240(GV900) 480(GV1000)	Smart Record Technology	240(GV900) 480(GV1000)	Smart Record Technology
Video Source	NTSC PAL	NTSC	NTSC	NTSC	NTSC
Video Format	320 x 240	320 x 240	320 x 240	320 x 240	320 x 240
Audio	4 channels	1 channel(GV600) 4 channels(GV900)	1 channel	1 channel 4 channels 16 channels	3 channels
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	6	7	8	9	10
Motherboard	ASUS P4PE	Shuttle FS50	FREE TECH P8F533	Gigabyte GA-8INXP	ASUS P4G8x
Chipset	845PE (North Bridge) ICH4 (South Bridge)	SIS 651 (North Bridge) SIS 961 (South Bridge)	845GE/GV (North Bridge) ICH4 (South Bridge)	E7205 (North Bridge) ICH4 (South Bridge)	E7205 (North Bridge) ICH4 (South Bridge)
CPU	Intel 3.06GHz (FSB 533)	Intel 2.66GHz (FSB 533)	Intel 1.4GHz (FSB 400)	Intel 3.06GHz (FSB 533)	Intel 3.06GHz (FSB 533)
VGA	ASUS (V8170) (64M) GeForce4 MX440	VGA on Board	VGA on Board	Albatron GeForce4 Ti4200	ASUS V9280 GeForce4 Ti4200
RAM	Kingmax 512MB DDR333	Kingmax 512MB DDR333	Kingston 512MB DDR200	Kingmax 256MB DDR400 X 2	Kingmax 512MB DDR333 x 2
HDD	IBM 80 GB	IBM 40 GB	IBM 40 GB	Maxtor 60 GB	IBM 80G
H/W	GV650 V1.07 card GV800 V1.07 card GV600 V3.01 card	GV800 V1.07 card	GV600 V2.08A card	1. GV600 V2.11 card 2. GV650 V1.07 card 3. GV800 V3.01 + DSP G1+GVA16	GV800 V1.07 card GV750 V1.07 card GV650 V3.01 card GV600 V3.01 card
S/W	V5300 V6000	V5300	V5300	1. V5300 2. V5301 3. V6000	V5301 V6000 V6020
O/S	English Windows 2000 Windows XPsp1	English Windows 2000	English Windows 2000	English Server 2003 Windows XP	English Windows 2000 Windows XP
Test Period	7 days (05/28~06/04) 13days (1/16~1/29)	10 days (05/29~06/08)	7 days (05/29~06/05)	7 days 1. (06/16~06/23) 2. (07/15~07/22) 14days (1/20~2/3)	7 days (06/30~07/07) (07/15~07/21) 14 days (1/20~2/3) 12 days (4/24~5/6)
Recording Mode	Round-The-Clock	Round-The-Clock	Round-The-Clock	Round-The-Clock	Round-The-Clock
CODEC	Wavelet GeoMpeg4	Wavelet	Wavelet	Mpeg-4 GeoMpeg4	Mpeg-4 GeoMpeg4
Frames / Sec	Smart Record Technology	Smart Record Technology	Smart Record Technology	Smart Record Technology	Smart Record Technology
Video Source	NTSC	NTSC	NTSC	NTSC	NTSC
Video Format	320 x 240	320 x 240	320 x 240	320 x 240	320 x 240
Audio	2 channels	4 channels	1 channel	1 channel 2 channels	4 channels 3 channels 2 channels
Note	1024*768 Resolution	Micro system	Micro system	1024*768 Resolution	1024*768 Resolution

No	11	12	13	14	15
Motherboard	Gigabyte GA-8IK1100	ASUS A7N8X-X	Albatron PX 865PE Pro	MSI 875P Neo LSR MS 6758	MSI 845PE MAX2-FIR
Chipset	875P (North Bridge) ICH5 (South Bridge)	N force Ultra400 (North Bridge) N force MCP (South Bridge)	865PE (North Bridge) ICH5 (South Bridge)	875P (North Bridge) ICH5 (South Bridge)	Intel 845PE (North Bridge) 82801DB (South Bridge)
CPU	Intel 2.6CGHz (FSB 800)	AMD XP2800+ Barton (FSB333)	Intel 2.8CGHz (FSB 800)	Intel 2.4CGHz (FSB 800)	Intel 2.4GHz (FSB 533)
VGA	Winfast A310TD Nvidia FX5600	ELSA 534 Nvidia FX5200	Albatron Giga FX5200P	MSI FX5200 TDR-128 MS-8907	GAINWARD GeForce 3 Ti500 64MB
RAM	A DATA 256MB DDR400 X 2	A DATA 256MB DDR400 X 2	Kingston 256MB DDR400 X 2	TwinMos 256MB DDR400 X 2	Kingmax 256MB DDR333
HDD	IBM 80 GB	Maxtor 80G	Maxtor 80 GB	Seagate 80 GB	Maxtor 60GB
H/W	GV900 V1.11 card GV1000 V1.11 card	GV804 V3.00 card	GV1000 V1.11 card GV900 V1.11 card	GV1000 V1.11 card	GV650 V3.01 + DSP G1 + GVA16
S/W	V5400	V5400	V6000	V6000	V6000
O/S	English Windows XP	English Windows 2000	English Windows XP	English Windows XP	English Windows 2000sp4
Test Period	9 days (8/29~9/7)	14 days (8/29~9/12)	7 days (11/24~12/01/) 30 days (2/12~3/14)	7 days (11/24~12/01)	8 days (1/28~2/5)
Recording Mode	Round-The-Clock	Round-The-Clock	Round-The-Clock	470~480(GV1000)	Round-The-Clock
CODEC	Wavelet M-Jpeg	Wavelet	Geo-Mpeg4	Geo-Mpeg4	Wavelet
Frames / Sec	230~240(GV900) 480(GV1000)	Smart Record Technology	477~480	475~480	Smart Record Technology
Video Source	NTSC	NTSC	NTSC	NTSC	NTSC
Video Format	320 x 240	320 x 240	320 x 240 640 x 240	320 x 240	640 x 240
Audio	4 channels	4 channels	4 channels	4 channels	2 channels
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	16	17	18	19	20
Motherboard	AOPEN AX4GER-N	Gigabyte GA-7NNXP	ASUS P4S-800 (SIS 648FX)	Aopen XC cube (Micro system)	GIGABYTE 8S655TX-ULTRA
Chipset	Intel 845GE (North Bridge) ICH4 (South Bridge)	N Force SPP (Ultra 400) (North Bridge) n Force MCP (South Bridge)	SIS 648FX (North Bridge) SIS 963L (South Bridge)	Intel 865G (North Bridge) ICH 5 (South Bridge)	SIS 655TX (North Bridge) SIS 964 (South Bridge)
CPU	Intel 2.4GHz (FSB 533)	AMD XP2800+ (Barton)	Intel 2.6CGHz (FSB 800)	Intel 2.6CGHz (FSB 800)	Intel 2.6CGHz (FSB 800)
VGA	Albatron GF4MX440SE-N	PowerColor R96-C3 (RADEON 9600)	GIGABYTE GV-R9500	VGA on Board	MSI TD128 MS-8912 (FX5600)
RAM	Kingmax 512MB DDR333	A DATA 256MB DDR400 X 2	Kingmax 512MB DDR333	Kingston 256MB DDR400 X 2	Kingston 256MB DDR400 X 2
HDD	Maxtor 60GB	Maxtor 80GB	WD 120GB	Maxtor 120GB (8M)	HITACHI 120GB 8M *2
H/W	GV600 V3.01 + GVA16	GV600 V2.11	GV 250 V2.1D	GV800 V3.01 card	GV1000 V1.11 card+ DSP G1 +GVA16
S/W	V6010	V6000	V6000	V6000	V6000
O/S	English Windows XP	English Windows XP	English Windows XP	English Windows 2000 sp4	English Windows XPsp1
Test Period	15 days (2/18~3/4)	8 days (12/10~12/17)	15 days (1/20 ~2/4)	9 days (1/7~1/16)	9 days (2/12~2/21)
Recording Mode	Round-The-Clock	Round-The-Clock	Round-The-Clock	Motion + WM	Round-The-Clock
CODEC	Mpeg4	Geo-Mpeg4	Geo-Mpeg4	Geo-Mpeg4	Geo-Mpeg4
Frames / Sec	Smart Record Technology	Smart Record Technology	Smart Record Technology	Smart Record Technology	470~480(GV1000)
Video Source	NTSC	PAL	NTSC	NTSC	NTSC
Video Format	320 x 240	320 x 240	320 x 240	640 x 480sw	320 x 240
Audio	1 channel	1 channel	1 channel	4 channels	16 channels
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	21	22	23	24	25
Motherboard	HP Desktop d330	GIGABYTE 8IPE1000-L	ASUS P4GE-V	CHAINTECH 9PJL	GIGABYTE 8IG1000-Pro
Chipset	Intel 865G (North Bridge) ICH 5 (South Bridge)	Intel 865PE (North Bridge) ICH 5R (South Bridge)	Intel 845GE (North Bridge) 82801DB (South Bridge)	Intel 865PE (North Bridge) ICH 5 (South Bridge)	Intel 865G (North Bridge) ICH 5 (South Bridge)
CPU	Intel 2.6CGHz (FSB 800)	Intel 2.8CGHz (FSB 800)	Intel 3.06CGHz (FSB 533)	Intel 2.8CGHz (FSB 800)	Intel 2.8CGHz (FSB 800)
VGA	VGA on Board	ELSA FX 736-128M (FX5700)	Aopen GF4MX440SE-N	ASUS V9560/TD (FX5600)	VGA on Board
RAM	A DATA 256MB DDR400 X 2	Kingston 256MB DDR400 X 2	Kingmax 512MB DDR333	Kingston 256MB DDR400 X 2	A DATA 256MB DDR400 X 2
HDD	HITACHI 120GB 8M *1 Seagate 120GB(8M) *1	Maxtor 120GB (8M) Maxtor(SATA) 160GB (8M)	WD WD 300BB 80GB (8M)	HITACHI 120GB (8M)	HITACHI 120GB (8M)
H/W	GV1000 V1.01 card GV 250 V2.2D	GV1000 V1.01 card+ DSP G1 +GVA16 GV650 V3.01 + DSP G1	GV 600 V3.01	GV 800 v3.01	GV800 V3.01+ DSP G1 GV900 V1.11+ DSP G1
S/W	V6000 V6020	V6000 V6020	V6020	V6020	V6000 V6020
O/S	English Windows XPsp1	English Windows XPsp1	English Windows XPsp1	English Windows XP	English Windows XPsp1
Test Period	21 days (2/16~3/8) 16 days (4/19~5/5)	28 days (2/10~3/9) 11 days (4/22~5/3)	35 days (3/16~4/20)	9 days (3/22~3/31)	9 days (2/3~2/12) 15 days (4/10~4/25)
Recording Mode	Round-The-Clock	Round-The-Clock	Round-The-Clock	Round-The-Clock	Round-The-Clock
CODEC	Geo-Mpeg4	Geo-Mpeg4	Mpeg4	Geo-Mpeg4	Mpeg4 Geo-Mpeg4
Frames / Sec	470~480(GV1000) Smart Record Technology	470~480(GV1000) Smart Record Technology	Smart Record Technology	Smart Record Technology	Smart Record Technology
Video Source	NTSC	PAL NTSC	NTSC	PAL	NTSC
Video Format	320 x 240	320 x 240	320 * 240	320 * 240	320 * 240
Audio	None 1 channel	16 channels 1 channel	1 channel	4 channels	4 channels
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	26	27	28	29	30
Motherboard	ASUS P4P800S	ACER Veriton 7600G	ASUS T2	GIGABYTE 8KNXP-ULTRA	AOPEN AX4SPE-UN
Chipset	Intel 848P (North Bridge) ICH 5 (South Bridge)	Intel 865G (North Bridge) ICH 5 (South Bridge)	Intel 865G (North Bridge) ICH 5 (South Bridge)	Intel 875P (North Bridge) ICH 5R (South Bridge)	Intel 865PE (North Bridge) ICH 5 (South Bridge)
CPU	Intel 2.8CGHz (FSB 800)	Intel 2.6CGHz (FSB 800)	Intel 2.6CGHz (FSB 800)	Intel 2.8CGHz (FSB 800)	P4 2.8C FSB 800 (Socket 478)
VGA	GAINWARD GFTi4800-SE 64MB	VGA on Board	VGA on Board	MSI FX5600XT-VTDR128 (FX5600XT)	ELSA 960XT-VIVO 128MB
RAM	TWIN MOS 512MB DDR400	TWIN MOS 256MB DDR400 *2	Kingston 256MB DDR400 *2	Kingston 256MB DDR400 *2	Kingston 256M *2 DDR400
HDD	HITACHI 120GB (8M)	HITACHI 120GB (8M)	HITACHI 120GB (8M)	SEAGATE 120GB (8M)	Hitachi 120G(P-ATA) HDS722512VLAT20 Maxtor(S-ATA) 160GB (8M) 6Y160M0-1A
H/W	GV804 V3.00	GV1000 V1.21 + GVA16 GV800 V3.01+ DSP G1+GVA16	GV800 V3.01	GV1000 V1.21 + DSP G1 + GVA16	GV1000 GV650
S/W	V6020	V6020	V6020	V6020	V6020 V6.1
O/S	English Windows XPsp1	English Windows XPsp1	English Windows XPsp1	English Windows XPsp1	E-Win-XPsp1
Test Period	19 days (4/2~4/21)	13 days (4/9~4/22) 21 days (5/3~5/24)	26 days (3/16~4/11)	19 days (4/9~4/28)	12 Days (6/15~6/27) 10 Days (10/1~10/11)
Recording Mode	Round-The-Clock	Round-The-Clock	Round-The-Clock	Round-The-Clock	Round the clock
CODEC	Geo-Mpeg4	Geo-Mpeg4	Mpeg4	Geo-Mpeg4	Geompeg4
Frames / Sec	Smart Record Technology	465~480(GV1000) Smart Record Technology	Smart Record Technology	475~480(GV1000)	465~480(GV1000) Smart Record Technology
Video Source	NTSC	NTSC	NTSC	NTSC	NTSC PAL
Video Format	320 * 240	320 * 240	320 * 240	320 * 240	320*240
Audio	4 channels	16 channels 4 channels	4 channels	16 channels	4 channels
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	31	32	33	34	35
Motherboard	AOPEN AX45F-4DN	ASUS P4P800-SE	GIGABYTE 8I865PE-TW	MSI 915G Combo-FR MS-7058 ver:1	ASUS P5GDC-V Deluxe
Chipset	SIS 655FX (North Bridge) SIS 964 (South Bridge)	Intel 865PE (North Bridge) ICH 5R (South Bridge)	Intel 865PE (North Bridge) ICH 5 (South Bridge)	Intel 915G (North Bridge) ICH 6R (South Bridge)	Intel 915G (North Bridge) ICH 6R (South Bridge)
CPU	P4 2.8C FSB 800 (Socket 478)	P4 2.8EG FSB800 (Socket 478) L2 1MB	P4 2.8EG FSB800 (Socket 478) L2 1MB	LGA775 P4 3.0G (Socket T)	LGA775 3.0G (Socket T)
VGA	AOPEN FX5700-DV128	ASUS A9550/TD/N/128M/A (ATI9550)	GIGABYTE GV-R955128D (ATI9550)	On board	On board
RAM	BUFFALO 256M *2 DDR400	Transcend 256MB *2 DDR400	Kingston 256MB *2 DDR400	Kingston 256MB *2 DDRII 533	A DATA 256MB *2 DDRII 533
HDD	Seagate 160GB(8M)PAT. ST3160023A 160GB(8M)SATA A ST-3160023AS	Seagate 160GB(8M)SATA ST-3160023AS *2	Seagate 160GB(8M)SATA ST-3160023AS Seagate 160GB(8M)PATA ST-3160023A	Seagate 160GB(8M)SATA ST-3160023AS *2	Seagate 160GB(8M)SATA ST-3160023AS *2
H/W	GV1000	GV800 GV900+DSP	GV1000	GV1000 GV800S	GV1000
S/W	V6020	V6.1	V6.1	V6.1 V7040	V6.1
O/S	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1
Test Period	12 Days (5/12~5/24)	10Days (8/7~8/17) 8 Days (8/18~8/26)	12 Days (8/13~8/25)	8 Days (9/22~9/30) 19Days (9/7 ~9/26)	11 Days (11/25~12/6)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	Geompeg4	Geompeg4	Geompeg4	Geompeg4	Geompeg4
Frames / Sec	GV1000 (465~480)	Smart Record Technology	GV1000 (465~480)	GV1000 (465~480) GV800S (120)	GV1000 (465~480)
Video Source	NTSC	PAL	PAL	NTSC	NTSC
Video Format	320*240	320*240	320*240	320*240	320*240
Audio		4 channels			
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	36	37	38	39	40
Motherboard	MSI 915P Neo2 Platinum MS-7028 VER:10A	GIGABYTE GA-8IPE100-G	ASUS P5AD2 Premium (925X)	Aopen AX4SPE Max2	GIGABYTE 8I915P-Duo
Chipset	Intel 915P (North Bridge) ICH 6R (South Bridge)	Intel 865PE (North Bridge) ICH 5 (South Bridge)	Intel 925X (North Bridge) ICH 6R (South Bridge)	Intel 865PE (North Bridge) ICH 5 (South Bridge)	Intel 915P (North Bridge) ICH 6R (South Bridge)
CPU	LGA775 2.8G (Socket T)	P4 3.0EG FSB800 (Socket 478) L2 1MB	LGA775 3.0G (Socket T)	P4 3.0EG FSB800 (Socket 478) L2 1MB	LGA775 3.0G (Socket T)
VGA	MSI PCX5750-TD12 8 8969 VER:1.0 (PCI-Express)	GIGABYTE GV-R955128D (ATI 9550)	ASUS Extreme AX600Pro/TD (ATI X600)	ASUS A9550/TD/N/128M (ATI 9550)	GIGABYTE GV-RX60X128V (ATI X600 XT)
RAM	A DATA 256MB *2 DDRII 533	APACER 256M *2 DDR400	A DATA 256MB *2 DDRII 533	A DATA 256M *2 DDR400	Kingston 256M *2 DDR400
HDD	Maxtor DiamondMax Plus9 160G *2 S-ATA	Hitachi 160G(P-ATA) HDS722516VLAT80 Seagate 160GB(8M)SATA ST-3160023AS	Seagate 160GB(8M)SATA *2 ST-3160023AS	Maxtor DiamondMax Plus9 160G P-ATA 160G S-ATA	Seagate 160GB(8M)SATA ST-3160023AS
H/W	GV900	GV800	GV1000	GV800	GV900 GV1000+GVA16 GV1480
S/W	V6.1	V6.1	V6.1 V7.0	V6.1	V7.0 V7020 V7040
O/S	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1
Test Period	24 Days (11/13~12/7)	24 Days (11/13~12/7)	13 Days (1/21 ~ 2/1) (2/4 ~ 2/14)	20Days (1/3 ~ 1/24)	10 Days 12 Days 19 Days
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	Geompeg4	Geompeg4	Geompeg4	Geompeg4	Geompeg4
Frames / Sec	GV900 (200~220)	Smart Record Technology	GV1000 (480)	GV900 (200~220)	GV900 (200~220) GV1000 (480) GV1480 (450)
Video Source	PAL	NTSC	NTSC	NTSC	PAL NTSC
Video Format	320*240	320*240	320*240	320*240	320*240
Audio	4 channels	4 channels		4 channels	16 channels
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	41	42	43	44	45
Motherboard	MSI 925X Neo Platinum MS-7053 Ver:1	GIGABYTE GA-K8N	MSI K8N Neo-FSR (nForce3 250)	GIGABYTE 8I915G-Duo	ASUS P4S800-MX
Chipset	Intel 925X (North Bridge) ICH 6R (South Bridge)	NVIDIA NFORCE3 150	NVIDIA NFORCE3 250	Intel 915G (North Bridge) ICH 6R (South Bridge)	SIS 661 FX (North Bridge) SIS 963L (South Bridge)
CPU	LGA775 3.0G (Socket T)	AMD Athlon 64 3000+ socket 754	AMD Athlon 64 3000+ socket 754	LGA775 3.0G(530) (Socket T)	P4 3.0EG FSB800 (Socket 478) L2 1MB
VGA	POWERCOLOR R37L Ver:3.0 128MB ATI X300	Powercolor R96 (ATI9550 256MB)	ELSA FX955 (ATI9550)	On Board	ASUS V9400 Magic (GF MX4000)
RAM	TwimOS 256MB *2 DDRII 533	Apacer 256MB*2 DDR400	ADATA 512M *1 DDR466	Kingston 256MB *2 DDRII 533	Kingston 256M *2 DDR400
HDD	Seagate 160GB(8M)SAT A ST-3160023AS	Hitachi 160G(P-ATA) HDS722516VLAT80	Seagate 160GB(8M)PATA ST-3160023A	Seagate 160GB(8M)SATA ST-3160023AS	Seagate 160GB(8M)SATA ST-3160023AS
H/W	GV650	GV800S	GV800S	GV1240 GV900+DSP G1	GV1120
S/W	V7.0	V7020	V7020	V7020 V6110	V7020
O/S	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1
Test Period	14Days (3/4 ~ 3/19)	13Days (6/3 ~ 6/16)	13Days (6/17 ~ 6/30)	10Days (6/7 ~ 6/16) 14 Days (10/20 ~ 11/3)	17Days (6/17 ~ 7/4)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	Geompeg4	Geompeg4	Geompeg4	Geompeg4	Geompeg4
Frames / Sec	GV650 Hybrid card*2	GV800 (90~100)	GV800 (90~100)	GV1240 Hybrid card*2 GV900 (240 FPS)	GV1120 (90~100)
Video Source	PAL	PAL	PAL	PAL NTSC	PAL
Video Format	320*240	320*240	320*240	320*240	320*240
Audio	4 channels	4 channels	4 channels	16 channels	16 channels
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	46	47	48	49	50
Motherboard	ASUS P5P800	Albatron PX865PEC-Pro	GIGABYTE 8IPE775-G	MSI 865PE Neo3-F	GIGABYTE GA-8I945P-G
Chipset	Intel 865PE (North Bridge) ICH 5 (South Bridge)	Intel 865PE (North Bridge) ICH 5 (South Bridge)	Intel 865PE (North Bridge) ICH 5 (South Bridge)	Intel 865PE (North Bridge) ICH 5 (South Bridge)	Intel 945P (North Bridge) ICH 7R (South Bridge)
CPU	LGA775 3.0G(530J) (Socket T)	LGA775 3.0G(530) (Socket T) not support 630	LGA775 3.0G(530) (Socket T)	LGA775 3.0G(530) (Socket T)	LGA775 3.0G(630) (Socket T)
VGA	ASUS A9550/TD/N/128M (ATI 9550)	ELSA 955 F1 (ATI 9550)	GeCube GC-Rx700PGA-C3 128MB GDDR3, (ATI X700 PRO)	MSI RX9550-TD128SP (ATI 9550)	GIGABYTE GV-RX70256D R38-PD3C
RAM	CORASIR 256M *2 DDR400	A DATA 256M *2 DDR433	A DATA 512M *2 DDR433	ADATA 256M *2 DDR433	Transcend 256MB DDR II *2
HDD	Seagate 160GB(8M)SATA ST-3160023A/P	Seagate 250GB (PATA) ST3250823ACE Seagate 160GB(PATA) ST3160022ACE	HITACHI T7K250 SATA II 3Gbps 160GB x1 Seagate 160GB(PATA) ST3160022ACE	Seagate 250GB (PATA) ST3250823ACE Seagate 160GB(PATA) ST3160022ACE	HITACHI T7K250 SATA II 3Gbps 160GB x1 250 GB x1
H/W	GV1480	GV800S 4A	GV1000 GV800S GV900+DSPG1	GV800S GV800 4A	GV1240 GV1480 GV900
S/W	V7020	V7020	V7020	V7040	V7040 V8.0
O/S	E-Win-XPsp1	E-Win-2Ksp4	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1
Test Period	11Days (5/20 ~ 6/1)	30Days (7/1 ~ 8/1)	7Days 18 Days 15 Days	10Days (12/2 ~ 12/12) 10Days (12/19 ~ 12/29)	10 Days 10 Days 12 Days
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	Geompeg4	Geompeg4	Geompeg4	Geompeg4	Geompeg4
Frames / Sec	GV1480 Hybrid card*4	(320*240) 100FPS (720*576)70~80FPS	GV1000+ Hybrid card*4 GV800S + Hybrid card*2	(320*240) 120 FPS (720*576)70~80FPS	GV1480 450FPS GV1240 240FPS GV900 240FPS
Video Source	NTSC	PAL	PAL	NTSC	NTSC PAL
Video Format	320*240	720*576	320*240	320*240	320*240 720*576
Audio	16 channels	4 channels	16 channels 12 channels	16 channels 4 channels	16 channels
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	51	52	53	54	55
Motherboard	ASUS P5ND2-SLI Deluxe	GIGABYTE GA-8N-SLI Royal	GIGABYTE GA-8I945GMF	Foxconn 945P7AA-8KS2	ASUS P5LD2-Deluxe-TAY
Chipset	NVIDIA NFORCE4 SLI Intel Enition (North Bridge) NVIDIA MCP-04 (South Bridge)	NVIDIA NFORCE4 SLI Intel Enition (North Bridge) NVIDIA MCP-04 (South Bridge)	Intel 945G (North Bridge) ICH 7 (South Bridge)	Intel 945P (North Bridge) ICH 7R (South Bridge)	Intel 945P (North Bridge) ICH 7R (South Bridge)
CPU	LGA775 3.0G(630) (Socket T)	LGA775 3.2G(640) (Socket T)	LGA775 3.2G(640) (Socket T)	LGA775 2.8G(820) (Socket T) Daul	LGA775 3.0G(630) (Socket T)
VGA	MSI RX600XT-TD128 /MS-8961	Winfast PX6600 TD 256MB	On board	ELSA 660LE	ASUS AX700PRO/TD, (ATI X700 PRO)
RAM	Transcend 256MB DDRII *2	Elixir 256MB DDRII *2	Elixir 256MB DDRII *2	Elixir 512MB DDRII *2	Apcaer 512M *2 DDR II 667
HDD	HITACHI T7K250 SATA II 3Gbps 160GB x1 250 GB x1	HITACHI T7K250 SATA II 3Gbps 160GB x1 250 GB x1	HITACHI T7K250 SATA II 3Gbps 160GB x1 250 GB x1	HITACHI T7K250 SATA II 3Gbps 160GB x1 250 GB x1	HITACHI T7K250 SATA II 3Gbps 160GB x1 250 GB x1
H/W	GV1000+DSP G1 GV800S+DSP G1 GV600S+DSP G1	GV1480 GV1248 GV800S	GV1120	GV800 4A GV600V3 GV250 V2.21	GV800 4A GV1480
S/W	V7040	V7040	V7040	V7040 V8.0	V8.0
O/S	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1	E-Win-XPsp1
Test Period	14Days 11Days 9 Days	12 Days 10 Days 15 Days	21 Days (10/4 ~ 10/25)	8 Days 13Days 10 Days	13Days (2/24 ~ 3/8)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	Geompeg4	Geompeg4	Geompeg4	Geompeg4	Geompeg4
Frames / Sec	GV1000 480FPS GV800S 100FPS GV600S 30FPS	GV1480 450FPS GV1240 240FPS GV800S 120FPS	GV1120+ Hybrid card*1	GV8004A 100 FPS GV600V3+ Hybrid card*2	GV8004A 100 FPS GV1480 450FPS
Video Source	NTSC PAL	PAL	PAL	PAL	NTSC PAL
Video Format	320*240	720*576	320*240	320*240	320*240
Audio	16 channels	4 channels	16 channels	4 channels 16 channels	4 channels 16 channels
Note	Need to upgrade Audio Driver WDM_A377.exe	Need to upgrade Audio Driver WDM_A377.exe	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	56	57	58	59	60
Motherboard	ASUS P5LD2-VM-TAY	Foxconn 945G7MA-8KS2	MSI 945P NEO-F	GIGABYTE 8I915PL-G DDR1 (915PL)	ASUS P5B
Chipset	Intel 945G (North Bridge) ICH 7 (South Bridge)	Intel 945G (North Bridge) ICH 7 (South Bridge)	Intel 945P (North Bridge) ICH 7R (South Bridge)	Intel 915PL (North Bridge) ICH 6 (South Bridge)	Intel P965 (North Bridge) ICH8 (South Bridge)
CPU	LGA775 3.2G(640) (Socket T)	LGA775 3.2G(640) (Socket T)	LGA775 2.8G (820) (Socket T) Dual	LGA775 3.2G(640) (Socket T)	LGA775 2.13G(E6400) (Socket T)
VGA	On Board	On Board	MSI NX6600-TD256E	GIGABYTE GV-NX62 TC256DS (6200 TC)	ASUS EAX1600XT SILENT/TVD
RAM	ADATA 256MB DDRII *2	Elixir 256MB DDRII *2	Elixir 512MB DDRII *2	Transcend 256MB *2 DDR400	Apacer 1GB DDRII 667*2
HDD	Seagate ST3250823AS SATAII 250G	HITACHI T7K250 SATA II 3Gbps 160GB x1 250 GB x1	HITACHI T7K250 SATA II 3Gbps 160GB x1 250 GB x1	Seagate ST3250823AS SATAII 250G	HITACHI Deskstar T7K250 250G(SATA II)
H/W	GV1480	GV1480 GV800 GV250	GV1480	GV1480	GV1480
S/W	V8.0	V8.0 V8010	V8020	V8.0	V8020
O/S	E-Win-XPsp1	E-Win-XPsp2	E-Win-XPsp2	E-Win-XPsp1	E-Win-XPsp1
Test Period	9 Days (3/7 ~ 3/16)	11 Days 10 Days 7 Days	18 Days (6/30 ~ 7/18)	9 Days (3/7 ~ 3/16)	14 Days
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	Geompeg4	Geompeg4	Geompeg4	Geompeg4	Geompeg4
Frames / Sec	GV1480 400FPS	GV1480 450FPS GV800 120FPS GV250 16FPS	GV1480 450FPS	GV1480+Mpeg2*2	480FPS
Video Source	PAL	NTSC	NTSC	NTSC	NTSC
Video Format	320*240	320*240	320*240	320*240	320*240
Audio	16 channels	16 channels	16 channels	16 channels	16 channels
Note	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution	1024*768 Resolution

No	61	62	63	64	65
Motherboard	MSI P965 Neo	GIGABYTE GA-965P-DS3	ASUS P5B-VM	ASUS P5B-VM DO	Gigabyte GA-G33-DS3R
Chipset	Intel P965 (North Bridge) ICH8 (South Bridge)	Intel P965 (North Bridge) ICH8 (South Bridge)	Intel G965 (North Bridge) ICH8 (South Bridge)	Intel Q965 (North Bridge) ICH8 (South Bridge)	Intel G33 (North Bridge) ICH9R (South Bridge)
CPU	LGA775 1.86G(E6300) (Socket T)	LGA775 2.4G(E6600) (Socket T)	LGA775 1.86G(E6300) (Socket T)	LGA775 1.86G(E6300) (Socket T)	LGA775 1.86G(E2160) (Socket T)
VGA	MSI RX1300PRO-TD256E/V040 (X1300)	GIGABYTE GV-NX76T256D-RH (NVIDIA 7600GT)	ON Board	ON Board	ON Board
RAM	ADATA 1GB DDRII 667*2	Transcend 1GB DDRII 667*2	Apacer 1GB DDRII 667*2	ADATA 512M DDR2-667*2	Transcend 1G DDRII 800*2
HDD	HITACHI Deskstar T7K250 250G(SATA II)	HITACHI Deskstar T7K250 250G(SATA II)	HITACHI Deskstar T7K250 250G(SATA II)	HITACH 160G HDS721616PLA380; 320G HDT725032VLA360	SEAGATE 160G T3160815AS SEAGATE 320G ST3320620AS
H/W	GV800S GV1480 PCI-E GV2008*1	GV650S V3.31 GV2008*2	GV650S V3.31 GV2008*1	GV800S V3.31 GV2008*2	GV2008*2
S/W	V8020	V8020 V8110 / V8120	V8020 V8110/V8120	V8110 V8120	V8120
O/S	E-Win-XP sp1	E-Win-XP sp2	E-Win-XP sp2	E-Win-XP sp2 E-Vista	E-Vista
Test Period	9 Days (9/18 ~ 9/27) 14 Days (9/28 ~ 10/12) 40 days (1/16 ~ 3/6)	7 Days (9/15 ~ 9/22) 30 days (1/16 ~ 2/16)	11 Days (9/22 ~ 10/3) 21 Days (1/25 ~ 2/15)	7 Days (4/13 ~ 4/20) 17 Days (4/20 ~ 5/7) 17 Days (7/11 ~ 7/28)	28 Days (8/30 ~ 9/28)
Recording Mode	Round the clock H/W MPEG4 ASP	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	Geompeg4	Geompeg4 H/W MPEG4 ASP	Geompeg4 H/W MPEG2	Geompeg4 H/W MPEG4 ASP	H/W MPEG4 ASP
Frames / Sec	GV800 120FPS GV1480 400FPS GV2008 240FPS	GV650 60FPS GV2008*2 480FPS	GV650 60FPS GV2008 240FPS	GV800 NTSC 120FPS PAL 100FPS GV2008*2 480FPS	GV2008*2 480FPS
Video Source	NTSC / PAL	NTSC / PAL	NTSC / PAL	NTSC / PAL	NTSC / PAL
Video Format	320*240 720*480	720*576 720*480	720*576 720*480	320*240 720*480	720*576
Audio	16 channels 8 channels	16 channels	16 channels 8 channels	16 channels	16 channels
Note	1024*768 Resolution	Update BIOS to "F8D" to resolve Combo Card DSP overlay problem	Combo Card Driver V1544 can resolve OS Freeze problem		

No	66	67	68	69	70
Motherboard	ASUS P5W64 WS Professional	ASUS P5KC	Supermicro C2SBE	Gigabyte GA-P31-DS3L	Gigabyte GA-73PVM-S2H
Chipset	Intel 975X (North Bridge) ICH7R (South Bridge)	Intel P35 (North Bridge) ICH9 (South Bridge)	Intel P35 (North Bridge) ICH9 (South Bridge)	Intel P31 (North Bridge) ICH7 (South Bridge)	NVIDIA 7300 (North Bridge) NVIDIA 630i (South Bridge)
CPU	Intel® Core™2 Extreme processor QX6700	LGA775 3.0G (E6850) (Socket T)	LGA775 Core 2 Quad Q6600 (Socket T)	LGA775 Core 2 Quad Q6600 (Socket T)	LGA775 Core 2 Quad Q6600 (Socket T)
VGA	GIGABYTE GV-RX16P256D-RH (ATI X1600)	Elsa 730GT 128B 3 2DT	ELSA NVIDIA 6600 LE	MSI NX8500GT-TD256 E-OC	On board
RAM	Kingstone DDRII 800 1G *2	ADATA 1G DDR2-800*2	ADATA 1G DDR2-800*2	Kingstone DDRII-800 1G*2	Kingstone DDRII-800 1G*2
HDD	WD2500YS SATA2 *2	SEAGATE 160G ST3160815SV SEAGATE 320G ST3320620SV	HITACHI 160G HDS721616PLA380 SEAGATE 320G ST3320620SV	HITACHI 160G HDS721616PLA380 SEAGATE 320G ST3320620SV	WD 160G WD1600AAJS SEAGATE 320G ST3320620SV
H/W	GV1480 GV2008*2	GV2008*2	GV2008*2	GV2008*2	GV1240
S/W	V8120	V8200	V8200	V8200	V8200
O/S	E-Win-XP sp2	E-Win-XP sp2	E-Win-XP sp2	E-Win-XP sp2	E-Win-XP sp2
Test Period	21 Days (5/15 ~ 6/6)	23 Day (12/14 ~ 1/10)	22 days (12/20 ~ 1/11)	16 days (1/30 ~ 2/15)	17 days (11/28 ~ 12/14)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	Geompeg4 H/W MPEG4 ASP	H/W MPEG4 ASP	H/W MPEG4 ASP	Geompeg4	Geompeg4
Frames / Sec	GV1480 480FPS GV2008*2 480FPS	480 FPS	480 FPS	480 FPS	240 FPS
Video Source	NTSC / PAL	NTSC	NTSC	NTSC	NTSC
Video Format	320*240 720*480	720*480	720*480	360*240	360*240
Audio	16 channels	16 channels	16 channels	16 channels	16 channels
Note					

No	71	72	73	74	75
Motherboard	DFI P35-T2RL	Foxconn P35A	Intel DG33BU	ASUS P5KPL-VM	Gigabyte GA-X38-DQ6
Chipset	Intel P35 (North Bridge) ICH9R (South Bridge)	Intel P35 (North Bridge) ICH9 (South Bridge)	Intel G33 (North Bridge) ICH9R (South Bridge)	Intel G31 (North Bridge) ICH7 (South Bridge)	Intel X38 (North Bridge) ICH9R (South Bridge)
CPU	LGA775 Core 2 Quad Q6600 (Socket T)	LGA775 Core 2 Quad Q6600 (Socket T)	LGA775 Core 2 Quad Q6600 (Socket T)	LGA775 Core 2 Dual E4400 (Socket T)	LGA775 Core 2 Quad QX6850 (Socket T)
VGA	ASUS X2600XT 256M DDR4	MSI RX2600PRO-T2D256 EZ/D3	On board	On board	Powercolor ATI1950 pro
RAM	Apcer DDRII-800 1G*2	Apcer DDRII-800 1G*2	Apcer DDRII-800 1G*2	ADATA 1G DDR2-800*2	Kingstone DDRII-800 1G*2
HDD	WD 160G WD1600AAJS SEAGATE 320G ST3320620SV	WD 160G WD1600AAJS SEAGATE 320G ST3320620SV	WD 160G WD1600AAJS SEAGATE 320G ST3320620SV	SEAGATE 160G ST3160815SV SEAGATE 320G ST3320620SV	HITACHI 160G HDS721616PLA3 SEAGATE 320G ST3320620SV
H/W	GV804A GV2008 *2	GV2008 *2	GV1240 GV2008 *2	GV1480 GV2008 *2	GV800 V4 GV2008 *2
S/W	V8200	V8200	V8200	V8200	V8200
O/S	E-Win-XP sp2	E-Win-XP sp2	E-Win-XP sp2	E-Win-XP sp2 E-Vista Ultimate	E-Win-XP sp2 E-Vista Ultimate
Test Period	17 Days (11/29 ~ 12/14) 24 Days (12/14 ~ 1/6)	25 Days (12/14 ~ 1/7)	15 Days (11/30 ~ 12/14) 24 Days (12/14 ~ 1/6)	25 Days (2/13 ~ 3/10) 27 Days (3/10 ~ 4/7)	15 Days (3/25 ~ 4/10) 32 Days (5/15 ~ 6/17)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	Geompeg4 H/W MPEG4 ASP	H/W MPEG4 ASP	Geompeg4 H/W MPEG4 ASP	Geompeg4 H/W MPEG4 ASP	Geompeg4 H/W MPEG4 ASP
Frames / Sec	GV804A 120FPS GV2008*2 480FPS	480 FPS	GV1240 240FPS GV2008*2 480FPS	480 FPS	GV800V4 120FPS GV2008*2 480FPS
Video Source	NTSC	NTSC	NTSC	NTSC	NTSC / PAL
Video Format	320*240 720*480	720*480	320*240 720*480	360*240 720*480	320*240 720*480
Audio	16 channels	16 channels	16 channels	16 channels	16 channels
Note					GV1480x2+Enhance ENP-5150G power supply causes distorted DSP live view and row data refreshing issue

No	76	77 Test180	79 Test189	80 Test193	81 Test195
Motherboard	ASUS P5E-VM HDMI	ASUS P5E-VM DO	MSI G31M2-FD	Gigabyte GA-X48-DQ6	ASUS P5Q-E
Chipset	Intel G35 (North Bridge) ICH9R (South Bridge)	Intel Q35 (North Bridge) ICH9 DO (South Bridge)	Intel G31 (North Bridge) ICH7 (South Bridge)	Intel X48 (North Bridge) ICH9R (South Bridge)	Intel P45 (North Bridge) ICH10R (South Bridge)
CPU	Intel Core 2 Duo E8400	LGA775 Core 2 Quad Q6600 (Socket T)	LGA775 Core 2 Quad Q6600 (Socket T)	Intel Core 2 QuadQ9450	Intel Core 2 QuadQ9300
VGA	On board	On board	On board	Gigabyte GV-RX365512HATI 3650	MSIRX3850-T2D512E (ATI 3850)
RAM	Adata DDRII-800 1G*2	ADATA 1G DDR2-800*2	Apecer DDRII-800 1G2	Apecer DDRII-800 1G2	Transcend DDRII-800 2G2
HDD	HITACHI 160G HDS721616PLA3 SEAGATE 320G ST3320620SV	HITACHI 160G HDS721616PLA380 SEAGATE 320G ST3320620SV	WD 160G WD1600AAJSSEAGAT E 320G ST3320620SV	WD 160G WD1600AAJSSEAGA TE 320G ST3320620SV	Seagate SATA160G SATA300G
H/W	GV2008 *2	GV2008 *2 GV1480A *2	GV2008 *2	GV2008 *2 GV1480A *2	GV2008 *2 GV1120A GV1480A
S/W	V8200	V8220 V8320	V8200	V8200 V8310	V8200 V8300 V8311
O/S	E-Win-XP sp2	E-Win-XP sp2 E-VISTA-UL	E-Win-XP sp2	E-Win-XP sp2 E-Vista-UL	E-Vista
Test Period	26 Days (4/30 ~ 5/26)	24 Days (7/31 ~ 8/22) 18 Days (09/28 ~ 10/10)	22 Days (7/1 ~ 7/22)	22 Days (7/1 ~ 7/22) 14 Days (08/18~09/01)	31 Days (7/4 ~ 8/5) 13 Days (09/22~10/05) 15 Days (10/09~10/21)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	H/W MPEG4 ASP	H/W MPEG2	H/W MPEG4 ASP	H/W MPEG4 ASP	GEOMPEG4 ASP H/W MPEG4 ASP
Frames / Sec	480 FPS	480 FPS	480 FPS	480 FPS	480 FPS
Video Source	NTSC / PAL	NTSC / PAL	NTSC / PAL	NTSC / PAL	NTSC / PAL
Video Format	720*480	720*480	720*480	720*480	720*480
Audio	16 channels	16 channels	16 channels	16 channels	16 channels
Note					

No	82 Test196	83 Test198	84 Test199	85 Test200	86 Test201
Motherboard	ASUS P5QL Pro	ASUS P5QL-EM	Gigabyte GA-EG45M-DS2H	ASUS P6T Deluxe	Gigabyte GA-EX58-UD5
Chipset	Intel P43 (North Bridge) ICH10 (South Bridge)	Intel G43 (North Bridge) ICH10 (South Bridge)	Intel G45 (North Bridge) ICH10R (South Bridge)	Intel X58 (North Bridge) ICH10R (South Bridge)	Intel X58 (North Bridge) ICH10R (South Bridge)
CPU	Intel Core 2 Quad Q9300 (2.5G)	Intel Core 2 Quad Q8200 (2.33G)	Intel Core 2 Quad Q8200 (2.33G)	Intel® Core™ i7 920	Intel® Core™ i7 920
VGA	WinFast PX9500 GT (GDDR3, Fan Edition)	On board	On board	PowerColor HD4830 512MB DDR3	Gigabyte GV-R465OC-1GI
RAM	PQI DDRII-1066 1G*2	Transcend DDRII-1066 1G*2	Transcend DDRII-1066 1G*2	Kingston DDRIII-1333 1G*2	ADATA DDRIII-1333 1G*2
HDD	HITACHI 160G HDS721616PLA380 HITACHI 500G HDP725050GLA360	WD 160G WD1600AAJS WD500G WD5000AACS	WD 160G WD1600AAJS WD500G WD5000AACS	WD 160G WD1600AAJS WD500G WD5000AACS	Hitachi 500G HDP725050GLA360
H/W	GV1480 *2 GV1120 *2 GV1480A *2	GV650 V4 *2 GV2008 *2 GV1480A *2	GV800 V4 *2 GV1480A *2 GV1008A *2 GV4008 *2	GV1480 *2 GV1480A *2	GV1480 *2 GV1480A *2
S/W	V8300 V8310	V8300 V8311	V8300 V8320	V8300 V8310	V8300 V8310
O/S	E-Win-XP sp2	E-Win-XP sp2 E-Server2003 E-WIN2K-SP4	E-Win-XP sp2 E-Vista	E-Win-XP sp2	E-Win-XP sp2 E-Win-XP-sp3
Test Period	20 Days (9/12 ~ 10/2) 14 Days (12/29 ~ 1/12) 14 Days (04/20~05/04)	14 Days (11/5 ~ 11/19) 24 Days (12/5 ~ 12/29) 13 Days (09/25~10/08)	17 Days (10/13 ~ 10/30) 14 Days (11/11 ~ 11/25) 13 Days (08/31 ~ 09/13) 11 Days (08/06 ~ 08/17)	37 Days (1/23 ~ 3/2) 16 Days (06/01~06/17)	37 Days (1/23 ~ 3/2) 10 Days 4/27~5/7
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	GEOMPEG4 ASP	GEOMPEG4 ASP. H/W MPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP
Frames / Sec	960 FPS / 240 FPS	120 FPS / 480 FPS	240 FPS / 960 FPS	800 FPS	960 FPS
Video Source	NTSC / PAL	NTSC / PAL	NTSC / PAL	PAL	NTSC
Video Format	320*240 / 720*480	320*240 / 720*480	320*240	320*240	320*240
Audio	32 channels	16 channels	32 channels	32 channels	32 channels
Note				8 Core System	8 Core System BIOS Update to F6C required

No	87 Test202	88 Test203	89 Test 205	90 Test 206	91 Test 207
Motherboard	Gigabyte GA-EG41MF-S2H	MSI P45 Neo2-2FR	Aspire M7720	Gigabyte GA-EQ45M-S2	Gigabyte EP45-UD3P
Chipset	Intel G41(North Bridge) ICH7(South Bridge)	Intel P45(North Bridge) ICH9(South Bridge)	Intel X58(North Bridge) ICH10R(South Bridge)	Intel Q45(North Bridge) ICH10 DO(South Bridge)	Intel P45(North Bridge) ICH10R(South Bridge)
CPU	LGA775 Core 2 Quad Q9300 (Socket T)	LGA775 Core 2 Quad Q6600 (Socket T)	Intel® Core™ i7 920	Intel Core 2 Quad Q8300	Intel Core 2 Quad Q9550 (2.83G)
VGA	On board	On board	ATI HD4850 (ATI X4850)	D-sub / DVI On board	MSI R4670-2D512SP 512M (ATI 4670)
RAM	PQI DDRII-1066 1G*2	PQI DDRII-1066 1G*2	Acer DDRIII-1333 1G*3	Transcend DDRII-800 1G*2	ADATA DDR2-1066 2GB*2
HDD	Hitachi 500G HDP725050GLA360	Hitachi 500G HDP725050GLA360	Seagate SATA500G	MAXTOR 500G STM3500320AS*2	Seagate 500G 3500418AS*2
H/W	GV1480A *2 GV2008 *2 GV800 *2	GV1480A *2	GV1480A *2	GV1480A *2 GV1008A *2	GV1120A *2
S/W	V8300	V8300	V8320	V8320	V8320
O/S	Win XP Vista	Vista	Vista	Win XP	Win XP
Test Period	14 Days (12/26 ~ 1/9) 11 Days (1/23~2/6) 13 Days (2/6~2/18)	37 Days (1/23 ~ 3/2)	14 Days (05/15~05/29)	14 Days (07/03~07/17) 21 Days (08/31~09/21)	14 Days (10/02~10/16)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP
Frames / Sec	960 FPS / 240 FPS	960 FPS	960 FPS	960 FPS	240 FPS
Video Source	NTSC / PAL	NTSC	NTSC	NTSC	NTSC / PAL
Video Format	320*240 / 720*480	320*240	320*240	320*240	320*240 / 720*480
Audio	32 channels	32 channels	32 channels	32 channels	32 channels
Note					

No	92 Test 208	93 Test 209	94 Test 210	95 Test 211	96 Test 220
Motherboard	Supermicro C2SBC-Q	MSI P7N SLI Platinum	MSI DKA790GX Platinum	MSI X58 Pro	Supermicro X8STE
Chipset	Intel Q35(North Bridge) ICH8(South Bridge)	nVidia 750i	AMD 790GX	Intel X58(North Bridge) ICH10R(South Bridge)	X58+ICH10R
CPU	Intel Core 2 Quad Q8300	Intel Core 2 Due E6300 (1.86G)	AMD Phenom™ II X4-920 (2.8G)	Intel® Core™ i7 920	Intel Core i7-920 (2.66G)
VGA	On board	ASUS EN9500GT/DI/1G (nVidia 9500)	On board	WinFast PX9800GT 512M	on board + ASUS ATI X2600
RAM	Corsair DDR2-800 2GB*2	Kingston DDRIII-1333 2G*2	Corsair DDR2-800 2GB*2	Kingston DDRIII-1333 2G*2	Adata DDR3-1333 2GB*2
HDD	Hitachi 500G HDP725050GLA360 *2	WD-500G 5001AALS*2	Hitachi 500G HDP725050GLA360*2	WD-500G 5001AALS*2	WD 500G WD5000AADS WD 1TB WD10EADS
H/W	GV4008 *2	GV800 *2	GV4008 *2 GV1120A *2 GV1480A *2	GV1120A *2 GV1008A *2	GV1480A GV4008 *2
S/W	V8320	V8310	V8320 V8311	V8320	V8320
O/S	Win XP Vista	Winxp	Winxp	Vista Winxp	Vista
Test Period	21 Days (08/06~08/27) 14 Days (09/30~10/13)	16 Days (06/06~06/24)	21 Days (08/06~08/27) 13 Days (09/22~10/05)	21 Days (07/21~08/17) 23 Days (08/31~09/22)	15 Days (09/25~10/10) 14 Days (10/16 ~ 10/30)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP
Frames / Sec	960 FPS	120 FPS	960/120 FPS	240/120 FPS	960 FPS
Video Source	PAL	NTSC	NTSC	NTSC	NTSC
Video Format	720*480	720*480	360*240	360*240	720*480
Audio	16 channels	32 channels	32 channels	32 channels	32 channels
Note					

No	97 Test 223	98 Test 212	99 Test 213	100 Test 214	101 Test 215
Motherboard	ASUS M4A785TD-M EVO	Gigabyte P55-UD3P	ASUS P7P55D	Gigabyte P55-UD4P	MSI P55-GD65
Chipset	AMD785G + SB710	Intel P55	Intel P55	Intel P55	Intel P55
CPU	AMD Phenom II X4 945 (3.0G)	Intel Core i5-750 (2.66G)	Intel Core i5-750 (2.66G)	Intel Core i7-860 (2.8G)	Intel Core i7-860 (2.8G)
VGA	on board	PowerColor HD4550 512MB DDR3	ASUS EAH4350 SILENT/DI/512MD2(L P)	Gigabyte GV-NX84S512HP PCI-E	MSI N9600GSO-MD512
RAM	KINGSTON DDR3-1333 1G*2	Adata DDR3-1333 2GB*2	Adata DDR3-1333 2GB*2	Corsair DDR3-1333 2GB*2	Corsair DDR3-1333 2GB*2
HDD	HITACHI 500G HDP725050GLA360 HITACHI (1TB) HDT721010SLA360	WD 500G WD5000AADS WD 1TB WD10EADS	WD 500G WD5000AADS WD 1TB WD10EADS	WD 500G WD5000AADS WD 1TB WD10EADS	WD 500G WD5000AADS WD 1TB WD10EADS
H/W	GV800 *2 GV1120A *2	GV1240A *2	GV4008 *2 GV1008A *2	GV1120A *2 GV4008 *2	GV1240A *2
S/W	V8320	V8320	V8320	V8320	V8320
O/S	Vista Windows 7 32 bit	Server 2008 32 bit Windows 7 32 bit	Windows 7 32 bit Server 2008 R2 64bit	Windows 7 32bit WINXP-SP2	Windows 7 32bit
Test Period	15 Days (10/06~10/21) 15 Days (12/18~01/02)	13 Days (12/20~01/02) 14 Days (01/02~01/16)	14 Days (12/02~12/16) 14 Days (01/29~02/12)	13 Days (12/02~12/15) 14 Days (01/18~02/01)	13 Days (12/24~01/05)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP
Frames / Sec	120 FPS	240 FPS	960 FPS	960 FPS / 120 FPS	240 FPS
Video Source	NTSC	NTSC	NTSC	NTSC	PAL
Video Format	720*480	720*480 360*240	720*480	720*480	720*576
Audio	32 channels	32 channels	32 channels	32 channels	32 channels
Note		<p>1. Only V8320 and later versions of GV-Video Capture Cards support PCs with Intel P55 Express Chipset.</p> <p>1. Only V8320 and later versions of GV-Video Capture Cards support PCs with Intel P55 Express Chipset.</p> <p>1. Only V8320 and later versions of GV-Video Capture Cards support PCs with Intel P55 Express Chipset.</p> <p>1. Only V8320 and later versions of GV-Video Capture Cards support PCs with Intel P55 Express Chipset.</p> <p>2. It is strongly recommended not to install the GV4008 Card to the last PCI-E 16X slot of ASUS P55 motherboards (gray color).</p>			

No	102 Test 217	103 Test 218	104 Test 219	105 Test229 New	106 Test230 New
Motherboard	ASUS P7P55D Pro	ASUS P7P55D Delux	Gigabyte P55-UD6	ASUS P7H57D-V EVO	ASRock H55DE3
Chipset	Intel P55	Intel P55	Intel P55	Intel H57	Intel H55
CPU	Intel Core i7-860 (2.8G)	Intel Core i7-860 (2.8G)	Intel Core i7-860 (2.8G)	Intel Core i5-661 (3.33G)	Intel Core i3-530 (2.93G)
VGA	ASUS EAH4550/DI/512M D3 PCI-E low profile	ASUS EAH4770FML/DI/512 D5	Gigabyte GV-R4350C-512I PCI-E	On board	On board
RAM	Adata DDR3-1333 2GB*2	Adata DDR3-1333 2GB*2	Adata DDR3-1333 2GB*2	PQI DDR3-1333 1GB*2	PQI DDR3-1333 1GB*2
HDD	WD 500G WD5000AADS WD 1TB WD10EADS	WD 500G WD5000AADS WD 1TB WD10EADS	WD 500G WD5000AADS WD 1TB WD10EADS	HITACHI 500G HDP725050GLA360 HITACHI (1TB) HDT721010SLA360	HITACHI 500G HDP725050GLA360 HITACHI (1TB) HDT721010SLA360
H/W	GV4008 *2	GV4008 *2 GV1480A *2	GV4008 *2 GV1480A *2	GV1480A *2	GV1480A *2
S/W	V8320	V8320	V8320	V8340	V8340
O/S	WINXP-SP3	VISTA-UL WINXP-SP2	VISTA-UL WINDOWS 7 64bit	WINXP-SP3	Win7 32bits
Test Period	13 Days (11/06~11/19)	13 Days (11/06~11/19) 14 Days (12/09~12/23)	13 Days (10/16~10/29) 14 Days (01/06~01/20)	14 Days 4/19 ~ 5/3	14 Days 4/19 ~ 5/3
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP
Frames / Sec	960 FPS	960 FPS	960 FPS	960 FPS	960 FPS
Video Source	NTSC	NTSC	PAL	NTSC	NTSC
Video Format	720*480	720*480 640*480	720*576 360*288	320*240	320*240
Audio	32 channels	32 channels	32 channels	32 channels	32 channels
Note	1. Only V8320 and later versions of GV-Video Capture Cards support PCs with Intel P55 Express Chipset. 2. It is strongly recommended not to install the GV4008 Card to the last PCI-E 16X slot of ASUS P55 motherboards (gray color).	1. Only V8320 and later versions of GV-Video Capture Cards support PCs with Intel P55 Express Chipset. 2. It is strongly recommended not to install the GV4008 Card to the last PCI-E 16X slot of ASUS P55 motherboards (gray color).	1. Only V8320 and later versions of GV-Video Capture Cards support PCs with Intel P55 Express Chipset.	Note: It is strongly recommended not to install the GV Combo A Card to the last PCI-E 16X slot of ASUS P55 motherboards (gray color).	

No	107 Test 232 New	108 Test 233 New	109 Test 234 New	110 Test 235 New
Motherboard	ASUS P7H55-M/USB3	MSI H55-GD65	ASROCK X58 Extreme6	Gigabyte GA-890GPA-UD3H
Chipset	Intel H55	Intel H55	Intel X58 (North Bridge) ICH10R (South Bridge)	AMD 890GX (North Bridge) SB850 (South Bridge)
CPU	Intel Core i7-875 (2.93G)	Intel Core i7-870 (2.93G)	Core i7 Extreme 980X 6 Core (3.33G)	Phenom II X6 1075T (3.0G)
VGA	ASUS EN210 Silent/DI/512MD3	MSI R5670-PMD1G/OC	ASUS EAH5770/2DI/512MD5	MSI N240GT-MD512-OC
RAM	ADATA DDR3-1333 2GB*2	ADATA DDR3-1333 2GB*2	ADATA DDR3-1333 2GB*2	ADATA DDR3-1333 2GB*2
HDD	WD 10EALS 1TB *2	WD 10EALS 1TB *2	WD 10EALS 1TB *2	WD 10EALS 1TB *2
H/W	GV1480*2	GV800A*2	GV1480*2	GV800A*2
S/W	V8.5 beta	V8.4.0.1	V8.5 beta	V8.4.0.1
O/S	Win7 X64	Win7 X86	Win7 X86	Win7 X86
Test Period	14 Days (2/8~2/22)	14 Days (12/22~1/5)	14 Days (12/22~1/5)	14 Days (2/8~2/22)
Recording Mode	Round the clock	Round the clock	Round the clock	Round the clock
CODEC	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP	GEOMPEG4 ASP
Frames / Sec	960 FPS	480 FPS	960 FPS	480 FPS
Video Source	NTSC	NTSC	NTSC	NTSC
Video Format	720*480	720*480	720*480	720*480
Audio	32 channels	32 channels	32 channels	32 channels
Note				